



Round head Phillips

PK716

PEEK



※PEEK characteristics:

UL94 V-0 compliant, highly incombustible.

Has excellent chemical resistance.

It is hardly eroded by drugs other than concentrated sulfuric acid, concentrated nitric acid, and concentrated hydrofluoric acid.

Body

Heat resistant temperature

PEEK
Brown

180°C

The usable temperature of the product varies depending on the conditions of use such as tightening torque.

How to order

PK716 - M1.2 - 4

TYPE M L

unit : mm

1		2																
M	Pitch	L												D	E	Torsional damage Torque(N· m)	Tensile damage Load (N)	
M1.2	0.25	2.5	4											1.8	0.5	0.01	45	
M1.4	0.3	2.5	4											2		0.015	50	
M1.6	0.35	2.5	4											2.3		0.018	55	
M1.7		2.5	4											2.5		0.02	59	
M2	0.4		4	5	6	8	10	12						3.5	1.3	0.06	160	
M2.6	0.45		4	5	6	8	10	12						4.5	1.7	0.16	312	
M3	0.5			5	6	8	10	12	15	16	20	25		5.5	2	0.3	430	
M4	0.7			5	6	8	10	12	15	16	20	25	30	40	7	2.6	0.64	765
M5	0.8					8	10	12	15	16	20	25	30		9	3.3	1.28	1230
M6	1						10	12	15	16	20	25	30		10.5	3.9	2.26	1670

※ The values in the table are for reference only and are not guaranteed. The recommended torque is 50% of the value in the table. 50 in (package)