



Round steel sheet long type

GL411

Stop payment fixed



Ontology

High strength aluminum alloy (White anode)

Disc.Pin

stainless steel

Hexagon socket head cap screws

SCM435 (Dye black)

How to order

GL411 - 20 - 5-8
 TYPE D d1xd2

													unit : mm	
D	Inner hole designation d1-d2		L	e	G	F	M	Max. torque (N·m)	Max. revolutions (rpm/min)	Moment of inertia (kg·m ²)	Static torsion spring coefficient (N·m/rad)	Allow eccentricity (mm)	Allowable declination (°)	weight g
	min.	max.												
16	3	~ 6	23.2	8	6.6	0.3	M2.5	0.9	6000	2.7×10 ⁻⁷	450	±0.2	2	12
20	5	~ 8	26	9	7.4			1.3	5500	8.0×10 ⁻⁷	700			26
25	5	~ 10	30.2	10.5	8	0.6	M3	2.8	5000	2.5×10 ⁻⁶	950	±0.3		45
32	8	~ 14	41	14.05	11.1	0.9	M4	5	4000	6.6×10 ⁻⁶	1100	±0.4		73
40	10	~ 18	47	16.9	10.8	1.2	M5	9	3800	1.9×10 ⁻⁵	2800	±0.5		100
50	10	~ 24	53	19.75	10.5	1.5		16	3500	5.0×10 ⁻⁴	3400	±0.6		193