



Round steel sheet long

GN411

Clamping



Ontology	Disc.Pin	Hexagon socket head cap screws
AL aluminum alloy (White anode)	stainless steel	SCM435 (Dye black)
SUS		SUS

How to order



Select the body material

AL-High strength aluminum alloy...
 SUS.....

D	Inner hole designation		L	e	G	F	H	M	Max. torque (N · m)		Allow eccentricity (mm)	Max. revolutions (rpm/min)	Moment of inertia (kg · m ²)		Static torsion spring coefficient (N · m/rad)		Allowable axial displacement (mm)	Allowable declination (°)	weight g
	min.	max.							AL	SUS			AL	SUS	AL	SUS			
	unit : mm																		
16	3	~ 6	23	7.35	2.5	1.8	4.9	M2	0.6	1	0.05	15000	2.3x10 ⁻⁷	5 x10 ⁻⁷	200	300	±0.2	1°	12
19	3	~ 8	27	9	3.3		5.2	M2.5	1	1.5	0.15		6.7x10 ⁻⁷	1.6x10 ⁻⁶	450	550			
25	3	~ 12	31	10.5	3.9	2.6	4.4	M3	2	3	0.2	10000	2.3x10 ⁻⁶	6.1x10 ⁻⁶	850	1100	±0.4	2°	38
28	3	~ 12	33	11.5					2.2	3.3			3.1x10 ⁻⁶	8.2x10 ⁻⁶	1000	1300			
32	3	~ 16	40	12.75	5	4.5	7.5	M4	4.2	6.3	0.25	9000	9 x10 ⁻⁶	2.5x10 ⁻⁵	1600	1800	±0.6	80	
40	8	~ 19	44	14.25					8	12			2.1x10 ⁻⁵	5.1x10 ⁻⁵	3200	3500			
50	8	~ 24	57	18.75	10.5	4.5	10.5	M5	10	15	0.3	9000	3.5x10 ⁻⁵	8.9x10 ⁻⁵	3900	5500	±0.8	160	
55	10	~ 32	61	19.75					25	37			1.4x10 ⁻⁴	2.9x10 ⁻⁴	9000	10000			300

Copyright © CHENA INDUSTRIAL CO.,LTD ALL RIGHTS RESERVED.