



Brass Ring - Cross


KL432

stop payment
fixed



ontology	Buffer	Buffer
SUS304	Aluminum Bronze	CM435 (blackened)

How to order



New JIS-B-1301

Keyway processing

example : KL432 - 20 - K5 x K6

D	L	d1 · d2		Df	LP	G	M	General Torque (N · M)	maximum torque (N · M)	Maximum speed (rpm/min)	moment of inertia (kg · m ²)	Static torsion spring constant (N · m/rad)	Allowable Axial Displacement	allowable deflection (°)	quality (g)	unit: mm
		min.	max.													
12	14.4	4	~ 6.35	0.25	4.0	2.5	M3	1.2	2.5	9000	2.0x10 ⁻⁷	250	±0.1	0.6	8.5	
14.5	16	4	~ 6.35	0.25	5.4	3			3	7000	4.5x10 ⁻⁷				800	
17	19.8	5	~ 8	0.25	6.3	3.2	M4	2.5	5	6500	1.0x10 ⁻⁶	900	±0.1	0.6	25	
20	21.4	5	~ 8	0.5	7.3				7	5000	2.25x10 ⁻⁶				2000	
26	25.6	5	~ 12	0.5	7.5	3.8	M5	5	10	5000	7.5x10 ⁻⁶	3500	±0.2	0.6	79	
30	33	5	~ 12	0.5	8.8	5.8			24	5000	2.5x10 ⁻⁵				5000	
34	34	5	~ 16	0.5	8.5	7.0	M5	5	32	3500	4.0x10 ⁻⁵	7500	±0.2	0.6	180	
38	39.5	5	~ 16	0.5	9.7				7.0	50	3500				5.2x10 ⁻⁵	
45	43.6	8	~ 22	1.5	13.6	7.5	M6	8	75	9000	1.7x10 ⁻⁴	65000	±0.3	0.2	400	
55	49.4	10	~ 25	1.5	15.4	8.5	M6	8	75	9000	3.3x10 ⁻⁴	90000	±0.5	0.2	750	
70	57	12	~ 35	2	17.0	11	M8	20	95	9000	1.1x10 ⁻³	170000	±0.6	0.2	1050	

Copyright © CHENA INDUSTRIAL CO., LTD ALL RIGHTS RESERVED.