





Parallel pins
WA708



DIN6885

Type	shape	Material
A	Flat	S45C
		SUS304
B	Unilateral round	S45C
		SUS304
C	Double round	S45C
		SUS304

How to order

WA708 - - 3 - 3 - 10 -

TYPE B H L

Type chosen

Flat.....

Unilateral round.....

Double round.....

Material chosen

S45C.....

SUS304.....

Unit : mm

1				2													3	C			
B	Tolerance	H	Tolerance	L																	
3	0 -0.025	3	0 -0.025	8	10	12	15	20	25	30	35	40								0.16 ~ 0.25	
4	0 -0.030	4	0 -0.030	8	10	12	15	20	25	30	35	40	45	50							
5		5		8	10	12	15	20	25	30	35	40	45	50							
6		6		8	10	12	15	20	25	30	35	40	45	50	60					0.25 ~ 0.40	
7	0 -0.036	7	0 -0.026	8	10	12	15	20	25	30	35	40	45	50	60	70					
8					10	12	15	20	25	30	35	40	45	50	60	70	80				
10						15	20	25	30	35	40	45	50	60	70	80					
12	0 -0.043	8	0 -0.090				20	25	30	35	40	45	50	60	70	80					
14									30	35	40	45	50	60	70	80	90	100			0.40 ~ 0.60
15										30	35	40	45	50	60	70	80	90	100		
16					10						30	35	40	45	50	60	70	80	90	100	

※ Make S45C hardness processing to HRC44~52, can marked **TH** at the material chosen.