

Hex head screw

PK713

PEEK

※PEEK characteristics:

UL94 V-0 compliant, highly incombustible.

Has excellent chemical resistance.

It is hardly eroded by drugs other than concentrated sulfuric acid, concentrated nitric acid, and concentrated hydrofluoric acid.



Body

Heat resistant temperature

PEEK
Brown

180°C

The usable temperature of the product varies depending on the conditions of use such as tightening torque.



How to order

PK713 - M4 - 12		
TYPE	M	L

1

2

unit : mm

M	Pitch	L											B	E	Torsional damage Torque(N·m)	Tensile damage Load (N)	
M4	0.7	8	10	12	15	20	25							7	2.8	0.64	756
M5	0.8		10	12	15	20	25	30						8	3.5	1.28	1230
M6	1		10	12	15	20	25	30	35	40	45	50		10	4	2.26	1670
M8	1.25		10	12	15	20	25	30	35	40	45			13	5.5	5.98	3090
M10	1.5				15	20	25	30	35	40	45			17	7	10.8	4900
M12	1.75					20	25	30	35	40	45	50	70	19	8	18.6	7360

※ The values in the table are for reference only and are not guaranteed. The recommended torque is 50% of the value in the table. 10 in (package)

Che Na

FAX 886-2688-3177

info@chena.com.tw

886-22688-3188
886-2688-3881~3No.21, Guangrong St. Shulin Dist.,
New Taipei City 238 Taiwan (R.O.C.)