


Steel plate high torque-short type

## SW416 Clamping



Ontology	disc-pin	Hexagon head screws
A6061 (white anode)	SUS	Steel+Ni

### How to order

1 2  
**SW416 - 56 - 11x14**  
TYPE      D      d1xd2

unit : mm																	
D	L	Bore designation d1-d2	Df	e	G	J	M	screw Locking force (N · m)	General torque (N · m)	Axial spring number	Maximum number of spins (rpm/min)	moment of inertia (kg · m <sup>2</sup> )	Allowable axis Displacement	Spring fixed number (N · m/rad)	allow eccentric	allow declination	quality (g)
56	43.9	10~17	4	20	3.9	5	8-M5	6	25	43	10000	12X 10 <sup>-5</sup>	0.4	16000			221
		18~25	1														
68	54.2	14~22	7	25	4.2	5.5	8-M6	12	60	45	10000	28X 10 <sup>-5</sup>	0.45	60000	0.02	1°	400
		24~30	2														
82	64.8	16~30	9	30	4.8	5.5	8-M6	12	90	60	10000	35X 10 <sup>-5</sup>	0.45	70000	0.02	1°	616
		32~35	6.5														
94	69.4	19~30	13	30	9.4	5.5	8-M6	14	180	120	10000	108X 10 <sup>-5</sup>	0.8	140000	0.02	1°	1000
		32~48	8														
104	70	24~50	13	30	10	5.5	8-M6	14	250	160	10000	115X 10 <sup>-5</sup>	0.8	160000	0.02	1°	1200
		55~60	3														