



Cross slider GC432

Cushion type fastening



Ontology	Cushioning material	Stop screw
AL High strength aluminum alloy (White anode)	PA66	CM435 (Dye black)

How to order

GC432 - 20 - 25 - 5x6
TYPE D L d1xd2

unit : mm										
D	L	Inner hole designation d1-d2 min. max.	e	M	G	Maximum torque (N · m)	Max. return speed (rpm/min)	Moment of inertia (kg · m ²)	Static torsion spring coefficient (N · m/rad)	Weight(g)
16	18	4 ~ 8	7.1	M3	3	0.7	9000	3.0x10 ⁻⁷	30	6
20	25	5 ~ 10	10.1	M4		1.2	7000		58	18
25	28	5 ~ 14	21		2.8	2	6000	130	25	
32	33	5 ~ 16	14		3.4	4.5	4800	270	44	
40	32	8 ~ 20			3.2	9	3600	520	81	
44	46	8 ~ 22	20.7	M5	3.5	12	3500	560	136	
50	38	10 ~ 25	16.5		3.8	19	3000	800	142	
55	57	10 ~ 32	26.2		7.8	22	2800	795	255	
70	77	16 ~ 40	36.5	M8	13.5	56	2500	1260	445	

Allowable axial displacement ±0.2mm , allowable declination:3°