


Pitch : 9.525mm

L



2 寬度代碼	037	050	075	100	150	200	單位質量 (寬度:1mm)
	9.5mm	12.7mm	19.1mm	25.4mm	38.1mm	50.8mm	
Ti 初張力 (N)	-	52	87	123	191	-	3.1 g/m
Td 下壓荷重 (N)	-	4	6.7	9.5	14.8	-	

材質	使用溫度
CR 合成橡膠	-10°C~50°C
PU 優力膠	-30°C~90°C



How to order

1 CR - 98 - L - 037
 材質 周長代號 寬度

選擇皮帶OPEN自由長
 例：優力膠
 OPEN-L-037-2.5M-PU

周長代號	皮帶周長		齒數
	inch	mm	
98-L	9.75	247.65	26
109-L	10.88	276.225	29
124-L	12.38	314.325	33
131-L	13.12	333.375	35
135-L	13.5	342.9	36
150-L	15	381	40
165-L	16.5	419	44
169-L	16.88	428.63	45
172-L	17.25	438.15	46
187-L	18.75	476.25	50
202-L	20.25	514.35	54
206-L	20.63	523.875	55
210-L	21	533.4	56
225-L	22.5	571.5	60
236-L	23.63	600.08	63
240-L	24	609.6	64
244-L	24.38	619.13	65
248-L	34.75	628.6	66
251-L	25.13	638.18	67
255-L	25.5	647.7	68
259-L	25.88	657.225	69
263-L	26.25	666.75	70
270-L	27	685.8	72
277-L	27.75	704.85	74
285-L	28.5	723.9	76
300-L	30	762	80
304-L	30.38	771.525	81
315-L	31.5	800.1	84
319-L	31.88	809.625	85
322-L	32.25	819.15	86

周長代號	皮帶周長		齒數
	inch	mm	
334-L	33.38	847.725	89
345-L	34.5	876.3	92
360-L	36	914.4	96
367-L	36.75	933.45	98
375-L	37.5	852.5	100
390-L	39	990.6	104
394-L	39.38	1000.125	105
405-L	40.5	1028.7	108
420-L	42	1066.8	112
427-L	42.75	1085.85	114
435-L	43.5	1104.9	116
450-L	45	1143	120
461-L	46.13	1171.58	123
465-L	46.5	1181.1	124
480-L	48	1219.2	128
510-L	51	1295.4	136
525-L	52.5	1333.5	140
540-L	54	1371.6	144
580-L	57.75	1466.85	154
581-L	58.13	1476.375	155
600-L	60	1524	160
619-L	61.88	1571.625	165
630-L	63	1600.2	168
660-L	66	1676.4	176
720-L	72	1828.8	192
731-L	73.83	1875.375	195
788-L	78.75	2000.25	210
863-L	86.25	2190.75	230
915-L	91.5	2324.1	244
1275-L	127.5	3238.5	340

※優力膠尺寸不齊，訂購前請先確認加納庫存。