

脫料板滾珠導套 STRIPPER GUIDE BUSHINGS



滾珠導套

	<p>FRA Loctite接著型</p> <table border="1"> <caption>溝距</caption> <thead> <tr> <th>L</th> <th>S1</th> <th>S2</th> </tr> </thead> <tbody> <tr> <td>20</td> <td>12</td> <td>-</td> </tr> <tr> <td>25</td> <td>16</td> <td>-</td> </tr> <tr> <td>30</td> <td>17</td> <td>-</td> </tr> <tr> <td>35</td> <td>15</td> <td>12</td> </tr> <tr> <td>40</td> <td>16</td> <td>16</td> </tr> </tbody> </table> <table border="1"> <tr> <td>M 材質</td> <td>SUJ2</td> </tr> <tr> <td>H 硬度</td> <td>HRC60-64</td> </tr> </table>	L	S1	S2	20	12	-	25	16	-	30	17	-	35	15	12	40	16	16	M 材質	SUJ2	H 硬度	HRC60-64
L	S1	S2																					
20	12	-																					
25	16	-																					
30	17	-																					
35	15	12																					
40	16	16																					
M 材質	SUJ2																						
H 硬度	HRC60-64																						
	<p>FRB Loctite接著型</p> <table border="1"> <caption>溝距</caption> <thead> <tr> <th>L</th> <th>S1</th> <th>S2</th> </tr> </thead> <tbody> <tr> <td>20</td> <td>5</td> <td>10</td> </tr> <tr> <td>25</td> <td>7</td> <td>11</td> </tr> <tr> <td>30</td> <td>8</td> <td>14</td> </tr> <tr> <td>35</td> <td>9</td> <td>17</td> </tr> <tr> <td>40</td> <td>10</td> <td>20</td> </tr> </tbody> </table> <table border="1"> <tr> <td>M 材質</td> <td>SUJ2</td> </tr> <tr> <td>H 硬度</td> <td>HRC60-64</td> </tr> </table>	L	S1	S2	20	5	10	25	7	11	30	8	14	35	9	17	40	10	20	M 材質	SUJ2	H 硬度	HRC60-64
L	S1	S2																					
20	5	10																					
25	7	11																					
30	8	14																					
35	9	17																					
40	10	20																					
M 材質	SUJ2																						
H 硬度	HRC60-64																						

版權所有
重製必究

Catalog No.		D	dR	L		
Type	PD					
FRA FRB	10	18	14	20	25	30
	13	22	17	20	25	30
	16	26	20	25	30	35
	20	31	26	30	35	40
	25	37	31	35	40	

訂購範例
Order

Catalog No.	-	L
FRA 16	-	20
FRB 16	-	25

交 期
Delivery

4	天出貨
---	-----

- 精度基準請參考P
- 以輕滑配或LOCTITE黏著固定