

脫料板導套 STRIPPER GUIDE BUSHINGS



給油型 oil type

FBA

FBA	外溝		內溝	
L	S1	S2	t1	t2
13	9	-	6.5	-
15	12	-	8	-
20	15	-	10	-
25	16	-	12.5	-
30	17	-	9	12
35	15	13	11	13
40	16	16	12	16

M 材質 SUJ2
H 硬度 HRC60-64

FBB

FBB	外溝		內溝	
L	S1	S2	t1	t2
13	8	-	6.5	-
15	10	-	8	-
20	5	10	10	-
25	7	11	12.5	-
30	6	18	9	12
35	7	21	11	13
40	8	24	12	16

M 材質 SUJ2
H 硬度 HRC60-64

版權所有 重製必究

D	C	Catalog No.		L						
		Type	d							
15	1	FBA	10	13	15	20				
18	1.5		13	13	15	20	25			
22		2	FBB	16	15	20	25	30	35	
26	20		20	25	30	35	40			
31	25		20	25	30	35	40			

銅鈦合金型 copper alloy oil type

MTA

M 材質 SUJ2銅鈦合金
H 硬度 HRC58
T 處理 高周波

D	H	Catalog No.		L					
		Type	d						
22	28	MTA	13	16	19	22	25		
25	31		16	16	19	22	25		
28	34		19	19	22	25			

MTB

M 材質 SUJ2銅鈦合金
H 硬度 HRC58
T 處理 高周波

D	Catalog No.		L					
	Type	d						
22	MTB	13	16	19	22	25		
25		16	16	19	22	25		
28		19	19	22	25			

訂購範例 Order Catalog No. - L
FBA 16 - 20
MTB 16 - 22

交 期 Delivery 4 天出貨

■ 精度基準請參考P
■ 以輕滑配或LOCTITE黏著固定