



精密固鎖螺帽

SBL-E

精密平衡用



How to order

① SBL-E - M20 - 1.5
TYPE 螺紋 Pitch

單位: mm

螺紋	Pitch	D	C	E	a	Ø b	f	M	鎖緊力矩 max. Nm	鬆脫力矩 Nm
M20	1	32	27	10	5	6 - M5	3	3-M5x0.8	4.5	24
M20	1.5									24
M25	1.5	38	33	12	6	9 - M5	4	3-M6x1.0	8	26.5
M30	1.5	45	40							28.4
M35	1.5	52	47	14	7	9 - M6	5			34.3
M40	1.5	58	52							36.3
M45	1.5	65	59	16	8	12 - M6	6			56.9
M50	1.5	70	64							63.7
M55	2	75	68	18	9	12 - M6	6			68.6
M60	2	80	73							96.1
M65	2	85	78	20	10	12 - M8	6	6-M8x1.25	18	112.7
M70	2	92	84							137.3
M75	2	98	90	22	11	12 - M8	6			145.1
M80	2	105	96							149
M85	2	110	102	24	12	12 - M8	6			168.6
M90	2	120	108							178.4
M95	2	125	113	26	13	12 - M8	6	6-M8x1.25	18	193.1
M100	2	130	118							210.8
M105	2	140	125	26	13	12 - M8	6	6-M10x1.5	35	215.7
M110	2	145	132							230.4
M115	2	150	137	26	13	12 - M8	6	6-M10x1.5	35	250
M120	2	155	142							264.7
M125	2	160	147	26	13	12 - M8	6	6-M10x1.5	35	274.5
M130	2	165	152							294.1
M135	2	175	160	26	13	12 - M8	6	6-M10x1.5	35	328.4
M140	2	180	165							372.5
M145	2	190	175	26	13	12 - M8	6	6-M10x1.5	35	402
M150	2	195	180							421.6

※此型螺帽不同於SBL-D型螺帽，在其平衡螺絲孔位於螺帽外圓，當平衡調整無法從背面調整時，此型為最佳替代品，配合消音螺絲，可降低高速所帶來的噪音問題。

※資料不及備載，其餘尺寸請洽伽納各窗口。