




鋼珠插銷

ZC616

三瓣型

球	銷	旋鈕	
		材質	使用溫度
SUS440C 55HRC	SUS303	工程塑膠 橘/黑	-30°C ~ 80°C

彈簧：SUS琴鋼線



How to order

ZC616 - 1 - 5 - 30
 TYPE 銷徑 長度

1											2				單位:mm			
d $\begin{smallmatrix} -0.04 \\ -0.08 \end{smallmatrix}$	E		L								A	B	C	D	對應孔建議尺寸		抗剪力 (KN)min.	質量 g
5	5.5	10	15	20	25	30					6				5	+0.06	24	30~32
6	7	10	15	20	25	30	40	50			7	31.5	38	16	6	-0	35	31~39
8	9.5			20	25	30	40	50			8				8		63	38~47
10	12				25	30	40	50	60		9				10	+0.08	100	76~97
12	14.5					30	40	50	60	70	10	36	43	23	12	-0	144	57~99

*L尺寸長短可訂製

Che Na

(FAX) (02)2688-3177

info@chena.com.tw

(02)2688-3188
(02)2688-3881~3




新北市樹林區光榮街21號

版權所有
重製必究

鋼珠插銷
ZC616
三瓣型

球	銷	旋鈕	
		材質	使用溫度
SUS440C 55HRC	SUS303	工程塑膠 橘/黑	-30°C ~ 80°C

彈簧：SUS琴鋼線



How to order

ZC616 - 5 - 30
TYPE 銷徑 長度

1										2				單位:mm			
d ^{-0.04} _{-0.08}	E	L								A	B	C	D	對應孔建議尺寸		抗剪力 (KN)min.	質量 g
5	5.5	10	15	20	25	30				6				5	+0.06	24	30~32
6	7	10	15	20	25	30	40	50		7	31.5	38	16	6	-0	35	31~39
8	9.5			20	25	30	40	50		8				8		63	38~47
10	12				25	30	40	50	60	9				10	+0.08	100	76~97
12	14.5					30	40	50	60	70	10	36	43	23	-0	144	57~99

*L尺寸長短可訂製